

MES-DEA SA - www.mes-dea.ch													
ZEBRA BATTERIES													
	Energy	Capacity	Voltage	Specific Energy	Energy Density	Specific Energy	Power Density	Peak Power	Thermal loss	Nr. of Cells	Dimensions	Weight	CLASS
	kWh	Ah	V	Wh / kg	Wh / L	W / kg	W / L	kW	W		mm	kg (BMI included)	
Z12-278-ML3X-152	42,3	152	278	120	191	181	288	64	165	432	1055 x 769 x 296	358	NORMAL
Z12-557-ML3X-64	35,7	64	557	101	160	181	288	64	165	432	1055 x 769 x 296	358	NORMAL
Z21-310-ML8X-50	15,5	50	310	112	168	171	257	24	< 115	240	1052 x 450 x 216	142	NORMAL
Z23-232-ML3X-76	17,6	76	232	120	177	170	252	25	< 90	180	826 x 450 x 296	152	NORMAL
Z36-371-ML3X-64	23,8	64	371	99	153	168	258	40	< 130	288	841 x 690 x 296	243	NORMAL
Z36-371-ML3X-76	28,2	76	371	118	181	168	258	40	< 130	288	841 x 690 x 296	243	NORMAL
Z37-310-ML3X-64	19,8	64	310	101	154	171	261	35,5	< 105	240	900 x 529 x 296	201	NORMAL
Z37-310-ML3X-76	23,5	76	310	119	183	170	261	33,5	< 105	240	900 x 529 x 296	201	NORMAL
Z37-620-ML3X-32	19,8	32	620	101	154	171	261	35,5	< 105	240	900 x 529 x 296	201	NORMAL
Z40-85-ML3X-418	35,6	418	85	119	210	89	155	26	< 150	363	1192 x 535 x 296	302	RESERVED
Z5-278-ML3X-64	17,8	64	278	100	152	179	273	30	< 105	216	826 x 530 x 296	182	PREFERRED
Z5-278-ML3X-76	21,2	76	278	119	181	169	257	30	< 105	216	826 x 530 x 296	182	PREFERRED
Z5-557-ML3X-32	17,8	32	557	100	152	179	273	30	< 105	216	826 x 530 x 296	182	PREFERRED
Z5-557-ML3X-38	21,2	38	557	119	181	169	257	30	< 105	216	826 x 530 x 296	182	PREFERRED
Z50-206-ML3X-38	7,8	38	206	117	164	177	247	12	< 52	80	463 x 421 x 296	72	SPECIAL
Z55T-263-ML3X-76	20	76	263	112	137	159	195	28,5	< 75	204	831 x 560 x 346	183	RESERVED
Z57-253-ML3X-76	19,2	76	253	120	177	170	251	27	< 105	196	683 x 608 x 296	165	NORMAL

Update: 22.12.2008
English version: 08.01.2009